





































Число жил и сечение n x mm <sup>2</sup> dimension n x mm <sup>2</sup>	Наружный диаметр mm outer Ø mm	Вес меди kg/km copper weight kg/km	Вес кабеля kg/km weight kg/km
2 X 0,5	8,1	38,0	117,0
3 G 0,5	8,4	45,0	135,0
4 G 0,5	9,2	54,0	150,0
5 G 0,5	9,9	62,0	173,0
7 G 0,5	11,9	76,0	198,0
12 G 0,5	14,4	131,0	313,0
18 G 0,5	17,0	175,0	408,0
25 G 0,5	20,2	223,0	638,0
2 X 0,75	8,5	46,0	135,0
3 G 0,75	8,9	56,0	149,0
4 G 0,75	9,7	67,0	169,0
5 G 0,75	11,0	78,0	197,0
7 G 0,75	12,8	97,0	315,0
12 G 0,75	15,6	168,0	410,0
18 G 0,75	17,7	229,0	560,0
25 G 0,75	21,7	296,0	762,0
2 X 1	9,2	52,0	150,0
3 G 1	9,7	66,0	163,0
4 G 1	10,6	79,0	198,0
5 G 1	12,4	93,0	239,0
7 G 1	13,7	117,0	335,0
12 G 1	16,4	204,0	522,0
18 G 1	19,4	280,0	628,0
25 G 1	22,6	369,0	855,0
2 X 1,5	10,1	69,0	181,0
3 G 1,5	11,1	87,0	205,0
4 G 1,5	12,6	102,0	240,0
5 G 1,5	13,5	125,0	286,0
7 G 1,5	15,3	180,0	383,0
12 G 1,5	19,2	281,0	690,0
18 G 1,5	22,2	391,0	806,0
25 G 1,5	25,1	518,0	1.180,0
2 X 2,5	11,3	112,0	191,0
3 G 2,5	12,7	123,0	298,0
4 G 2,5	14,2	168,0	345,0
5 G 2,5	15,0	204,0	457,0
7 G 2,5	17,5	265,0	561,0
12 G 2,5	21,7	421,0	857,0
18 G 2,5	25,5	598,0	1.053,0
25 G 2,5	29,4	848,0	1.373,0

Число жил и сечение n x mm <sup>2</sup> dimension n x mm <sup>2</sup>	Наружный диаметр mm outer Ø mm	Вес меди kg/km copper weight kg/km	Вес кабеля kg/km weight kg/km
2 X 4	14,1	120,0	247,0
4 G 4	16,0	238,0	527,0
5 G 4	17,3	302,0	661,0
7 G 4	19,0	396,0	828,0
2 X 6	16,1	180,0	353,0
4 G 6	17,7	318,0	715,0
5 G 6	19,0	419,0	832,0
7 G 6	22,1	559,0	1.205,0
2 X 10	18,4	256,0	492,0
4 G 10	21,7	574,0	864,0
5 G 10	23,8	714,0	1.020,0
4 G 16	25,2	809,0	1.184,0
5 G 16	27,6	1.053,0	1.402,0
4 G 25	29,8	1.165,0	1.792,0
5 G 25	32,7	1.446,0	2.209,0
4 G 35	32,7	1.683,0	2.495,0
5 G 35	38,7	1.975,0	2.736,0
4 G 50	39,6	2.368,0	4.094,0
5 G 50	44,9	2.880,0	5.118,0
4 G 70	44,0	3.261,0	5.467,0
5 G 70	50,4	4.032,0	6.834,0
4 G 95	51,0	4.055,0	5.849,0
5 G 95	56,5	5.264,0	7.720,0
4 G 120	58,1	5.225,0	7.509,0