

PPLVDV-af/2af

Alternative designations:
 RE-2X(St)2YMYbY-PiMF
 XLPE/PSCR/OSCR/PE/LC/PVC/SWA/
 PVC

Characteristics:
 - 7 wire conductors
 - shielded pairs
 - shielded cable core
 - lead sheath
 - armoured

Construction:

conductors:

soft-annealed, plain electrolytic copper, 7 wires stranded to form a flexible conductor.

insulation:

XLPE (cross-linked polyethylene), 0.4mm nominal thickness.

pairs, numbered*:

2 cores twisted into a pair.
 Core colours are white and black.

shielding of pairs (PPLVDV-2af):

- 1 layer of polyester foil,
- 1 layer of polyester/aluminium foil with a solid tinned copper earth wire 0.6mm dia.,
- 1 layer of polyester foil.

communication core*:

0.5 mm² (7x0.31 mm dia.), with orange XLPE insulation.

shielding of cable core:

- 1 layer of polyester foil,
- 1 layer of polyester/aluminium foil with tinned copper earth litz wire (7x0.31 mm dia.),
- 1 layer of polyester foil.

inner sheath:

PE (polyethylene)

lead sheath:

extruded, snugly fitting lead sheath, 1.3mm nominal thickness.

inner sheath:

PVC

armouring:

round or flat galvanised steel wires (depending on the cable diameter) and open-pattern counterwound galvanised steel strip.

outer sheath:

flame-retardant PVC, sheath colour is black or blue.

standards:

(as far as applicable): IEC 189, 228, 228A, 332-3C and 502.
 KEMA standard K102 and draft CENELEC specifications for instrumentation cables.

**) Lacking on single-pair PPLVDV-af cables.*



PPLVDV-2af